









A perfect fit

- Height max. 250 cm, extension max. 400 cm (dependent on fabric and height)
- Centimetre-accurate manufacture in all intermediate sizes
- Manual operation

Installation:

- Wall mounting (standard)
- Post to screw into base (with or without base console)



Private refuge – well protected from prying eyes and annoying draughts.

The Micro 700 forms the perfect complement to a glass roof or awning (shown here with Murano Integrale glass roof from Lewens).

The Micro 700 side screen awning provides shelter from the sun, wind and unwanted attention, creating a snug refuge on the patio, balcony or loggia. The Micro 700 complements conventional sunshades or glass roofs in terms of function and design. The fabrics of all Lewens products can be perfectly coordinated with one another.

When the side screen is retracted, the cassette can simply be removed from the bracket to protect against theft and vandalism and can be stored safely until next required.

Installation

Wall mounting (standard)



Screwed to base (instead of standard)



Screwed to base with base console



Micro 700

Equipment and technical features





Manufactured and assembled in Germany



Quality and technology CE-compliant

Unit height (max.) 1 unit (single panel) 250 cm Extension (max., depending on fabric and height) Acrylic/ (recycled) polyester 400 cm *300 cm *300 cm Soltis 92 400 cm 400 cm *300 cm *300 cm Theight (max.) Soltis 92 400 cm 400 cm *300 cm						
Tunit (single panel) Extension (max., depending on fabric and height) Acrylic/(recycled) polyester Acrylic/(recycled) polyester 400 cm *300 cm *300 cm Soltis 92 400 cm 400 cm *300 cm *3	Wall cassette (W x D)	108,8 x 100,6	mm			
Extension (max., depending on fabric and height) Acrylic/(recycled) polyester Acrylic/(recycled) polyester 400 cm *300 cm *300 cm Soltis 92 400 cm 400 cm *300 cm *300 cm *300 cm *300 cm *300 cm *300 cm Drive Manual operation, 1 handle Manual operation, further handles Frame colours 29 Lewens standard frame colours Additional RAL, special colours and effect finishes Awning fabrics from the LEWENS collection Branded acrylic (spun-dyed, ultra fade resistant) Soltis 92 Branded polyester/recycled polyester (spun-dyed, ultra fade resistant) Tenara quality sewing yarn Ultrasonic seam welding Attachment Wall mounting	Unit height (max.)					
Acrylic/[recycled] polyester 400 cm *300 cm *300 cm Soltis 92 400 cm 400 cm *300 cm *3	1 unit (single panel)	250	cm			
Soltis 92 400 cm 400 cm *300 cm Drive Manual operation, 1 handle Manual operation, further handles Frame colours 29 Lewens standard frame colours Additional RAL, special colours and effect finishes Awning fabrics from the LEWENS collection Branded acrylic (spun-dyed, ultra fade resistant) Soltis 92 Branded polyester/recycled polyester (spun-dyed, ultra fade resistant) Tenara quality sewing yarn Ultrasonic seam welding Attachment Wall mounting	Extension (max., depending on fabric and height)	Height up to 134	cm	Up to 190	cm	Up to 250 cm
Manual operation, 1 handle Manual operation, further handles Frame colours 29 Lewens standard frame colours Additional RAL, special colours and effect finishes Awning fabrics from the LEWENS collection Branded acrylic (spun-dyed, ultra fade resistant) Soltis 92 Branded polyester/recycled polyester (spun-dyed, ultra fade resistant) Tenara quality sewing yarn Ultrasonic seam welding Attachment Wall mounting	Acrylic/(recycled) polyester	400	cm	*300	cm	*300 cm
Manual operation, 1 handle Manual operation, further handles Frame colours 29 Lewens standard frame colours Additional RAL, special colours and effect finishes Awning fabrics from the LEWENS collection Branded acrylic (spun-dyed, ultra fade resistant) Soltis 92 Branded polyester/recycled polyester (spun-dyed, ultra fade resistant) Tenara quality sewing yarn Ultrasonic seam welding Attachment Wall mounting	Soltis 92	400	cm	400	cm	*300 cm
Manual operation, further handles Frame colours 29 Lewens standard frame colours Additional RAL, special colours and effect finishes Awning fabrics from the LEWENS collection Branded acrylic (spun-dyed, ultra fade resistant) Soltis 92 Branded polyester/recycled polyester (spun-dyed, ultra fade resistant) Tenara quality sewing yarn Ultrasonic seam welding Attachment Wall mounting	Drive					
Frame colours 29 Lewens standard frame colours Additional RAL, special colours and effect finishes Awning fabrics from the LEWENS collection Branded acrylic (spun-dyed, ultra fade resistant) Soltis 92 Branded polyester/recycled polyester (spun-dyed, ultra fade resistant) Tenara quality sewing yarn Ultrasonic seam welding Attachment Wall mounting	Manual operation, 1 handle					
Additional RAL, special colours and effect finishes Awning fabrics from the LEWENS collection Branded acrylic (spun-dyed, ultra fade resistant) Soltis 92 Branded polyester/recycled polyester (spun-dyed, ultra fade resistant) Tenara quality sewing yarn Ultrasonic seam welding Attachment Wall mounting	Manual operation, further handles					
Additional RAL, special colours and effect finishes Awning fabrics from the LEWENS collection Branded acrylic (spun-dyed, ultra fade resistant) Soltis 92 Branded polyester/recycled polyester (spun-dyed, ultra fade resistant) Tenara quality sewing yarn Ultrasonic seam welding Attachment Wall mounting	Frame colours					
Awning fabrics from the LEWENS collection Branded acrylic (spun-dyed, ultra fade resistant) Soltis 92 Branded polyester/recycled polyester (spun-dyed, ultra fade resistant) Tenara quality sewing yarn Ultrasonic seam welding Attachment Wall mounting	29 Lewens standard frame colours					
Branded acrylic (spun-dyed, ultra fade resistant) Soltis 92 Branded polyester/recycled polyester (spun-dyed, ultra fade resistant) Tenara quality sewing yarn Ultrasonic seam welding Attachment Wall mounting	Additional RAL, special colours and effect finishes					
Soltis 92 Branded polyester/recycled polyester (spun-dyed, ultra fade resistant) Tenara quality sewing yarn Ultrasonic seam welding Attachment Wall mounting	Awning fabrics from the LEWENS collection					
Branded polyester/recycled polyester (spun-dyed, ultra fade resistant) Tenara quality sewing yarn Ultrasonic seam welding Attachment Wall mounting	Branded acrylic (spun-dyed, ultra fade resistant)					
Tenara quality sewing yarn Ultrasonic seam welding Attachment Wall mounting	Soltis 92					
Ultrasonic seam welding Attachment Wall mounting	Branded polyester/recycled polyester (spun-dyed, ultra fade	resistant)				
Attachment Wall mounting	Tenara quality sewing yarn					
Wall mounting	Ultrasonic seam welding					
	Attachment					
Post for screwing into base	Wall mounting					
	Post for screwing into base					
Post for screwing into base with base console \Box	Post for screwing into base with base console					

Possible dimensions and restrictions along with complete range of accessories can be found in the technical data in the current Lewens price list.

■ Standard □ Option * only vertical web processing



Your stockist will be happy to advise you:

